

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 25/06, 25/00		A1	(11) International Publication Number: WO 99/16498
			(43) International Publication Date: 8 April 1999 (08.04.99)
(21) International Application Number: PCT/US98/20309 (22) International Filing Date: 29 September 1998 (29.09.98) (30) Priority Data: 60/060,624 1 October 1997 (01.10.97) US (71) Applicant: BOSTON SCIENTIFIC LIMITED [US/BB]; Financial Services Centre, P.O. Box 111, Bishops Court Hill, St. Michael (BB). (72) Inventor: DAVEY, Christopher, T.; 100 Paul Gore Street, Boston, MA 02130 (US). (74) Agent: CHIU, Jerrie, L.; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).			(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: **PERCUTANEOUS CATHETER WITH SLIP HUB**



(57) Abstract

A "slip" hub design is used with catheters to reduce flexure motion at the hub to catheter shaft connection. The design includes a hub having a section of reduced diameter and having a longitudinal axis extending along the length of the hub. The reduced diameter section has a first length. The design also includes a suture wing component having a first portion with a lumen. Wings extend from the first portion, and in use are sutured to the skin of a patient, or to an anchoring device that is secured to the skin of a patient. The lumen has a second length that is less than the first length. The reduced diameter section of the hub is disposed within the lumen such that the axis extends through the lumen and such that the hub and the suture wing component are movable relative to each other both axially along the axis and rotationally about the axis.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

PERCUTANEOUS CATHETER WITH SLIP HUB

Cross-Reference to Related Application

This incorporates by reference and claims priority to and the benefit of U.S. provisional patent application serial number 60/060,624, filed October 1, 1997.

5

Technical Field

The invention relates generally to catheters for use in a body. More particularly, the invention relates to a "slip" hub design for use in a percutaneous catheter in a body.

Background Information

Long term indwelling percutaneous catheters, such as peripherally-inserted central catheters (PICCs), central lines, and hemodialysis catheters, are widely used for a variety of medical applications (e.g., administration of drugs, drawing blood, etc.). These catheters have a rigid hub that is typically sutured to the skin to prevent the catheter shaft from being inadvertently pulled out. More specifically, suture wings are rigidly connected to the hub and sutured to the skin. The catheter shaft extends from the sutured hub, through the skin and underlying tissue, into the vascular system and ends at the junction of the superior vena cava and the right atrial (i.e., the SVC/RA junction). The catheter is maintained in this position over several weeks or months.

During this period of time, the patient is typically fully ambulatory. Since the hub is rigidly fixed to the patient (i.e., via the suture wings) and the catheter shaft is relatively fixed within the percutaneous entry site, all relative motion between these two locations imparts flexural stress on the hub to catheter shaft connection. As the patient moves about over the period of time (e.g., several weeks or months) that the catheter is in use, the rigid connection between the hub and patient focuses all the resulting flexural motion on the hub to catheter shaft connection. Over time, this stress often leads to mechanical failure at

- 2 -

the hub to catheter shaft junction, which requires the removal and replacement of the failed catheter. For example, an article entitled "PICC Lines: Choosing Devices, Placement and Management" by Dr. Alan Matsumoto reports a 9.7% mechanical failure rate of the device at the hub to catheter shaft junction.

- 3 -

Summary of the Invention

It is a principle object of the invention to reduce the mechanical failure rate of catheters, such as long term indwelling percutaneous catheters. It is another object of the invention to provide a long term indwelling percutaneous catheter that offers a flexible
5 connection between the hub and suture wings such that a percentage of the flexural motion is absorbed at that area, thereby reducing the stress on the hub to catheter shaft connection and extending the service life of the catheter.

These and other objects are met by a "slip" hub design according to the invention. With catheters employing this type of new hub design, the rate of mechanical failure of the
10 catheters (such as long term indwelling percutaneous catheters) is reduced, and the catheters can be maintained in position in patients' bodies for an extended period of time, such as several weeks, several months, or longer.

The invention features a catheter (such as a long term indwelling percutaneous catheter) that includes an elongated catheter shaft, a hub, and a suture wing component.
15 The elongated shaft has a proximal end and a distal end, where the distal end is for insertion into a body. The distal end of the catheter shaft enters the body at an entry site. The entry site can be a puncture of the skin of the body that leads to a vein within the body into which the catheter shaft is inserted, for example. The hub is located at or near the entry site of the body. A suture wing component is placed over (and surrounds) a portion
20 of the hub. The suture wing component is secured to the skin of the body, or to an anchoring device that is itself secured to the skin of the body, adjacent the entry site. The catheter shaft extends through the hub, through the skin and underlying tissue, and into the vascular system (e.g., into a vein) of the patient's body such that the distal tip of the catheter shaft can be located at a desired point in the body, such as at the SVC/RA
25 junction. The catheter can be maintained in this position within the body for an extended

- 4 -

period of time, such as for several weeks, several months, or longer. The hub includes a section of reduced diameter, which is engaged and surrounded by a portion of the suture wing component. The reduced diameter section allows the hub to move substantially unrestricted translationally (i.e., axially, back and forth along a longitudinal axis of the hub
5 and catheter) and rotationally relative to the suture wing component. In one embodiment, the suture wing component includes a rounded edge adjacent the hub. The rounded edge of the suture wing component allows an additional degree of freedom of relative movement between the hub and the suture wing component, such that the hub can "rock" within the suture wing component.

10 The foregoing and other objects, aspects, features, and advantages of the invention will become more apparent from the following description and from the claims.

- 5 -

Brief Description of the Drawings

In the drawings, like reference characters generally refer to the same parts throughout the different views. Also, the drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention.

5 FIG. 1 is a cross-sectional view taken along section B-B of FIG. 2 of a long term indwelling percutaneous catheter incorporating the principles of the invention.

FIG. 2 is a cross-sectional view taken along section A-A of the catheter of FIG. 1.

FIG. 3 is a partial cross-sectional view of an alternative embodiment suture wing component in a long term indwelling percutaneous catheter.

10 FIG. 4 shows a catheter generally, such as an indwelling percutaneous catheter.

- 6 -

Description

In one aspect, the invention relates to a catheter comprising an elongated member, such as a catheter shaft, a hub, and suture wing component. The elongated member includes a proximal end and a distal end, the distal end being insertable into a body at an entry site of the body. The hub is connected to the proximal end of the elongated member, and it is disposed at the entry site. The hub includes a section of reduced diameter, and a longitudinal axis extends along the length of the hub. The suture wing component is for securing to the body adjacent the entry site. Alternatively, the suture wing component can be secured or attached to an anchoring device that is itself secured to the skin of the body adjacent the entry site. The suture wing component surrounds a portion of the reduced diameter section of the hub at the entry site, thereby enabling the hub to move both along and about the axis relative to the suture wing component.

In another aspect, the invention features a system comprising a hub and a suture wing component. The hub is for use with a catheter. The hub includes a section of reduced diameter and has a longitudinal axis extending along its length. The reduced diameter section has a first length. The suture wing component has a first portion with a lumen and wings extending from that first portion. The lumen has a second length that is less than the first length. The reduced diameter section of the hub is disposed within the lumen such that the axis extends through the lumen and such that the hub and the suture wing component are movable relative to each other both axially along the axis and rotationally about the axis.

In some embodiments of the invention, the suture wing component comprises a rounded edge that allows the hub to have additional freedom of movement relative to the suture wing component, such that the hub can "rock" within the suture wing component.

- 7 -

In general, according to the invention, a "slip" hub design is provided for a flexible catheter 2, such as a long term indwelling catheter, including a percutaneous central venous catheter. The catheter 2 is shown generally in FIG. 4 outside of the body. A "slip" hub of the invention has a section of reduced diameter, which allows the hub to
5 move in a substantially unrestricted manner relative to suture wings, which in use are sutured to the patient's skin. A "slip" hub design of the invention better distributes flexural stresses among the patient's skin, the catheter shaft, and the catheter hub. The "slip" hub reduces flexure motion at the hub to catheter shaft connection and thus reduces the frequency of field failures resulting from the catheter breaking from the hub.

10 FIG. 1 is a cross-sectional view taken along section B-B of FIG. 2 of a long term indwelling percutaneous catheter 2 that includes a "slip" hub design of the invention. As shown in FIG. 4, the catheter shaft 10 has a proximal end 12, and a distal end 14, which is for placement within the body of the patient. As shown in FIGS. 1 and 4, the hub 16 is located at or near an entry site of the body, and a suture wing component 18 is located
15 over or about the hub 16. A portion of the suture wing component 18 surrounds a portion of the hub 16 that has a reduced diameter. That is, the suture wing component 18 has a first portion with a lumen, and the reduced diameter section 20 of the hub 16 is disposed within this lumen such that the lumen and the hub are coaxial with respect to the longitudinal axis 15. The suture wing component 18 fits in this reduced diameter section
20 20 of the hub 16, but it fits in a way that it has some "play" to allow relative movement, both axial and rotational, between the hub 16 and the suture wing component 18. The hub 16 can be an integral part of the catheter 2, the catheter 2 and the hub 16 can be disconnectable from each other, or the hub 16 can be assembled to the catheter 2 in such a way that they are practically unremovable from each other in the field. Different assembly,
25 connection/disconnection, and manufacturing schemes generally are known, and the actual assembly details are generally less central to the invention than the ability provided by the

- 8 -

invention to have both longitudinal and axial relative motion between the hub 16 and the suture wing component 18.

When the suture wing component 18 is not attached (e.g., sutured) to the skin of the patient, or not attached to an anchoring device that is itself secured to the skin of the patient, the suture wing component 18 can substantially freely spin or rotate within the reduced diameter section 20 of the hub 16 about the longitudinal axis 15, and it also can substantially freely move back and forth (i.e., axially with respect to the longitudinal axis 15) within the travel range of the reduced diameter section 20 of the hub 16. In one embodiment, the travel range is 5 millimeters or about 5 millimeters. In one embodiment, the diameter of the reduced diameter section 20 of the hub 16 is between about 1 millimeter to about 3 millimeters, and preferably it is 2 millimeters or about 2 millimeters. The suture wing component 18 has at least one pre-formed hole or puncture 19 near the end of each wing to allow attachment (e.g., suturing) to the skin of the patient to hold the suture wing component 18 secure when the catheter 2 is in use and in place within the body. When secured to the skin, or to an anchoring device that is secured to the skin, the suture wing component 18 stays substantially stationary, and movement of the patient and/or the catheter 2 typically will result in the hub 16 rotating within the suture wing component 18 about the axis 15 and moving axially back and forth with respect to the axis 15 over all or a portion of the travel range of the reduced diameter section 20 of the hub 16. Another view of the suture wing component 18 is shown in FIG. 2.

In use, the catheter shaft 10, which extends into and typically through the hub 16, enters the body via an entry site of a body, such as, for example, a puncture of the skin of the body. One example of a catheter of the invention would be a percutaneous central venous catheter having the "slip" hub design. The distal portion of the shaft of percutaneous central venous catheter can extend through the skin and underlying tissue, into the vascular system (e.g., a vein), and end at the SVC/RA junction. Because of the

- 9 -

“slip” hub design, the catheter can be maintained in this position for a period of several weeks, several months, or longer, without the mechanical failure associated with conventional indwelling catheters.

The reduced diameter section 20 of the hub 16 thus allows the hub 16 to move in a substantially unrestricted manner back and forth (i.e., longitudinally or axially along the axis 15) and rotationally (i.e., about the axis 15) relative to the suture wing component 18.

FIG. 3 shows an embodiment of the invention in which the suture wing component 18 has a rounded edge 22 adjacent the reduced diameter section 20 of the hub 16. The rounded edge 22 allows the hub 16 to “rock” within the suture wing component 18. Like the other hub design (FIGS. 1 and 2), this alternative design also reduces the flexure motion at the hub to catheter shaft connection, and acts to extend the service life of the catheter.

The invention allows for greater relative motion between the hub 16 and the suture wing component 18 than possible with conventional catheters. With the invention, flexural forces can be distributed over two junctions (suture wing component to hub and, catheter shaft to hub), rather than just one (catheter shaft to hub), thus extending the life of the catheter. In one embodiment, the amount of relative motion permitted between the hub 16 and suture wing component 18 may be limited to much less than one square centimeter of the patient’s skin surface, which would have little or no impact on the catheter’s distal tip location within, for example, the SVC/RA junction. This motion, however, greatly reduces the flexing and stress associated with conventional catheters.

Variations, modifications, and other implementations of what is described herein will occur to those of ordinary skill in the art without departing from the spirit and the scope of the invention as claimed. Accordingly, the invention is to be defined not by the

- 10 -

preceding illustrative description but instead by the spirit and scope of the following claims:

What is claimed is:

- 11 -

Claims

- 1 1. A catheter, comprising:
 - 2 an elongated member including a proximal end and a distal end, the distal
 - 3 end being insertable into a body;
 - 4 a hub connected to the proximal end of the elongated member, the hub
 - 5 including a section of reduced diameter, a longitudinal axis extending along the
 - 6 length of the hub; and
 - 7 a suture wing component for being secured to an external portion of the body, the
 - 8 suture wing component surrounding a portion of the reduced diameter section of the hub
 - 9 at the entry site thereby enabling the hub to move both along and about the axis relative to
 - 10 the suture wing component.
- 1 2. The catheter of claim 1 wherein the suture wing component comprises a
- 2 rounded edge thereby allowing the hub to have additional freedom of movement relative
- 3 to the suture wing component.
- 1 3. The catheter of claim 1, wherein said suture wing component is configured to
- 2 be attachable to an anchoring device secured to skin of said body.
- 1 4. A system, comprising:
 - 2 a hub for use with a catheter, the hub including a section of reduced diameter and
 - 3 having a longitudinal axis extending along the length of the hub, the reduced diameter
 - 4 section having a first length; and

- 12 -

5 a suture wing component having a first portion with a lumen and wings extending
6 from the first portion, the lumen having a second length less than the first length, the
7 reduced diameter section of the hub disposed within the lumen such that the axis extends
8 through the lumen and such that the hub and the suture wing component are movable
9 relative to each other both axially along the axis and rotationally about the axis.

1 5. The system of claim 4, wherein the suture wing component comprises a
2 rounded edge thereby allowing the hub to have additional freedom of movement relative
3 to the suture wing component.




Fig. 1

2/4




Fig. 2




Fig. 3

4/4




Fig. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/20309

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61M25/06 A61M25/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 589 361 A (LOPER ET AL.) 29 June 1971 see abstract see column 2, line 14 - line 52 see column 3, line 11 - line 35 see column 4, line 61 - line 75 see column 5, line 26 - line 37; figures 1,2,5-11	1-5
A	US 5 088 982 A (RYAN) 18 February 1992 see abstract see column 2, line 16 - line 63; figures 1-3,5A,B -/-	1-5

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

20 January 1999

Date of mailing of the international search report

28/01/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Michels, N

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/20309

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 5 330 449 A (PRICHARD ET AL.) 19 July 1994 see abstract see column 1, line 30 - line 66 see column 3, line 39 - column 4, line 14; figures 4-6</p>	1-5
A	<p>US 4 392 856 A (LICHTENSTEIN) 12 July 1983</p>	

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. National Application No

PCT/US 98/20309

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3589361 A	29-06-1971	DE 1929050 A FR 2010558 A GB 1243576 A	11-12-1969 20-02-1970 18-08-1971
US 5088982 A	18-02-1992	US 5059185 A US 4923445 A AU 3071689 A CA 1324546 A CN 1035955 A,B DE 68908584 D DE 68908584 T EP 0331452 A JP 2071757 A JP 2791082 B US 5067945 A US 5085639 A US 5154699 A US 5066287 A	22-10-1991 08-05-1990 07-09-1989 23-11-1993 04-10-1989 30-09-1993 24-02-1994 06-09-1989 12-03-1990 27-08-1990 26-11-1991 04-02-1992 13-10-1992 19-11-1991
US 5330449 A	19-07-1994	NONE	
US 4392856 A	12-07-1983	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.